



BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 7/15/2026 Revision date: 7/15/2026

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : BadAss Super Sheen Tire Shine
Product code : BadAss BA9503
Aerosol : Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Automotive Care Products.
Recommended use : Includes tire dressing, gloss, restorers.
Restrictions on use : None

1.4. Supplier's details

Petra Automotive Products, Inc.
11085 Regency Green Dr.
Cypress, TX 77429
USA
T (713) 856-5700
www.petraautoproducts.com

1.5. Emergency phone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only): CHEMTREC 1-800-424-9300 (in the US), 1-703-527-3887 (Outside the US)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H222 - Extremely flammable aerosol
H229 - Pressurized container; may burst if heated
H304 - May be fatal if swallowed and enters airways

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Precautionary statements (GHS US)	H315 - Causes skin irritation
	H319 - Causes serious eye irritation
	H336 - May cause drowsiness or dizziness
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P261 - Avoid breathing vapors, spray, mist.
	P264 - Wash hands thoroughly after handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P280 - Wear protective gloves, protective clothing, eye protection.
	P301+P310 - If swallowed: Immediately call a poison center or doctor.
	P331 - Do NOT induce vomiting.
	P302+P352 - If on skin: Wash with plenty of water.
	P332+P313 - If skin irritation occurs: Get medical attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
	P312 - Call a poison center or doctor if you feel unwell.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 - If eye irritation persists: Get medical attention.
	P403 - Store in a well-ventilated place.
	P405 - Store locked up.
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
	P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

Prolonged or repeated contact may dry skin and cause irritation

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

Mixtures

Name	Product identifier	Conc. (% w/w)
Acetone	CAS-No.: 67-64-1	30 – 60
tert-butyl acetate	CAS-No.: 540-88-5	10 – 30
Carbon dioxide (CO2)	CAS-No.: 124-38-9	7 – 15
heptane, n-heptane	CAS-No.: 142-82-5	5 – 10

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Move the affected person to fresh air. Get medical attention if symptoms occur.

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. Get medical advice if skin irritation persists. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth out with water. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	: Aspiration hazard. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.
Inhalation	: May cause respiratory irritation. High concentration of vapors may induce: headache, nausea, dizziness. Intentional abuse may be harmful or fatal.
Skin	: Causes skin irritation.
Eyes	: Causes serious eye irritation.
Ingestion	: Aspiration hazard. May be fatal if swallowed and enters airways. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Chronic symptoms	: No chronic health hazards are likely for this material.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: If accidentally swallowed obtain immediate medical attention. Aspiration hazard. May be fatal if swallowed and enters airways.
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Use dry chemical, CO ₂ , water spray or alcohol-resistant foam.
Unsuitable extinguishing media	: None.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Keep away from open flames, hot surfaces and sources of ignition. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Exposure to fire may cause containers to rupture/explode.
Explosion hazard	: Contains gas under pressure; may explode if heated. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Hydrocarbon. Carbon oxides (CO, CO ₂).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Use shielding to protect from bursting cans.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate all ignition sources. Ventilate area. Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.
------------------	--

For non-emergency personnel

Emergency procedures	: No open flames, no sparks, and no smoking. Ventilate area. Avoid breathing mist, Spray, vapors. Avoid contact with skin and eyes. Keep unnecessary and unprotected personnel away from the spillage.
----------------------	--

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

For emergency responders

- Protective equipment
- : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Environmental precautions
- : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

- For containment
- : Collect spillage.
- Methods for cleaning up
- : Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Absorb and/or contain spill with inert material, then place in suitable container. Notify authorities if product enters sewers or public waters.
- Other information
- : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling
- : Ensure adequate ventilation. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wear personal protective equipment. Avoid breathing mist, Spray, vapors. Avoid contact with eyes, skin and clothing. Pressurized container: Do not pierce or burn, even after use. Handle in accordance with good industrial hygiene and safety procedures.
- Hygiene measures
- : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including incompatibilities

- Storage conditions
- : Store in a cool, well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store locked up. U.F.C. (NFPA 30B) Level II Aerosol.
- Incompatible materials
- : Strong oxidizers. Direct sunlight. Sources of ignition.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Acetone (67-64-1)	
USA - ACGIH® - Threshold Limit Values	
Local name	Acetone
ACGIH® TLV® TWA	594 mg/m³
	250 ppm
ACGIH® TLV® STEL	1187 mg/m³
	500 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2026

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Acetone (67-64-1)

USA - ACGIH® - Biological Exposure Indices

Local name	Acetone
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2026

USA - OSHA - Occupational Exposure Limits

Local name	Acetone
OSHA PEL (TWA)	2400 mg/m ³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

Carbon dioxide (CO2) (124-38-9)

USA - ACGIH® - Threshold Limit Values

Local name	Carbon dioxide
ACGIH® TLV® TWA	9000 mg/m ³
	5000 ppm
ACGIH® TLV® STEL	54000 mg/m ³
	30000 ppm
Remark (ACGIH®)	TLV® Basis: Asphyxia
Regulatory reference	ACGIH 2026

USA - OSHA - Occupational Exposure Limits

Local name	Carbon dioxide
OSHA PEL (TWA)	9000 mg/m ³
	5000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

heptane, n-heptane (142-82-5)

USA - ACGIH® - Threshold Limit Values

Local name	Heptane, isomers (n-Heptane)
ACGIH® TLV® TWA	200 ppm
ACGIH® TLV® STEL	400 ppm
Remark (ACGIH®)	TLV® Basis: URT irr; Lung dam; CNS impair; Ototoxicity. Notations: OTO (Ototoxicant)
Regulatory reference	ACGIH 2026

USA - ACGIH® - Biological Exposure Indices

Local name	Heptane, isomers (n-Heptane)
BEI (BLV)	140 µg/l Parameter: 2,5-Heptanedione - Medium: urine - Sampling time: End of exposure
Regulatory reference	ACGIH 2026

USA - OSHA - Occupational Exposure Limits

Local name	Heptane (n-Heptane)
OSHA PEL (TWA)	2000 mg/m ³

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

heptane, n-heptane (142-82-5)

	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

tert-butyl acetate (540-88-5)

USA - ACGIH® - Threshold Limit Values

Local name	tert-Butyl acetate
ACGIH® TLV® TWA	238 mg/m³
	50 ppm
ACGIH® TLV® STEL	712 mg/m³
	150 ppm
Remark (ACGIH®)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2026

USA - OSHA - Occupational Exposure Limits

Local name	tert-Butyl-acetate
OSHA PEL (TWA)	950 mg/m³
	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Provide adequate general and local exhaust ventilation.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Materials for protective clothing:

Wear suitable protective clothing

Hand protection:

Chemically resistant protective gloves. Consult supplier for specific recommendations.

Eye protection:

Chemical goggles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Thermal hazard protection:

Not applicable.

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol can. Clear, colorless liquid.
Color	: Colorless
Odor	: Solvent-like aliphatic
Odor threshold	: Not determined
pH	: Not applicable
Melting point	: Not applicable
Freezing point	: Not determined
Boiling point	: Not determined
Flash point	: -20 °C Acetone
Relative evaporation rate (butyl acetate=1)	: > 1
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: Not determined
Relative vapor density at 20°C	: No data available
Relative density	: 0.79 – 0.83
Solubility	: Insoluble. Water: 0 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: Not determined
Explosion limits	: Lower explosion limit: 2.5 Vol-% Acetone Upper explosion limit: 36 Vol-% Methanol
Explosive properties	: Not determined.
Oxidizing properties	: Not oxidising.
Particle characteristics	: Particle characteristics : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	: 9.6 %
-------------	---------

SECTION 10 Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Protect from sunlight. Do not puncture or incinerate containers.

10.5. Incompatible materials

Keep away from oxidizers, strong acids and strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg
LC50 Inhalation - Rat	76 mg/l

Carbon dioxide (CO2) (124-38-9)

LC50 Inhalation - Rat [ppm]	167857 ppm
-----------------------------	------------

heptane, n-heptane (142-82-5)

LD50 oral rat	> 5000 mg/kg body weight
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LD50 dermal	3000 mg/kg
LC50 Inhalation - Rat	> 29300 mg/m³
LC50 Inhalation - Rat (Vapors)	25132 ppmv

tert-butyl acetate (540-88-5)

LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity)
--------------------	--

Skin corrosion/irritation : Causes skin irritation.
pH: Not applicable
Serious eye damage/irritation : Causes serious eye irritation.
pH: Not applicable
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Acetone (67-64-1)

LOAEL (animal/female, F0/P)	11298 mg/kg body weight mouse
NOAEL (animal/male, F0/P)	900 mg/kg body weight rat
STOT-single exposure	: May cause drowsiness or dizziness.

Acetone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

heptane, n-heptane (142-82-5)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified

heptane, n-heptane (142-82-5)

LOAEC (inhalation,rat,vapor,90 days)	16.6 mg/l air Animal: rat, Animal sex: male
NOAEC (inhalation,rat,vapor,90 days)	3.3 mg/l air Animal: rat, Animal sex: male

Aspiration hazard : May be fatal if swallowed and enters airways.

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

BadAss Super Sheen Tire Shine	
Aerosol	Aerosol
Viscosity, kinematic	Not determined
Symptoms/effects	: Aspiration hazard. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.
Inhalation	: May cause respiratory irritation. High concentration of vapors may induce: headache, nausea, dizziness. Intentional abuse may be harmful or fatal.
Skin	: Causes skin irritation.
Eyes	: Causes serious eye irritation.
Ingestion	: Aspiration hazard. May be fatal if swallowed and enters airways. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Not expected to present a significant ingestion hazard under anticipated conditions of normal use.
Chronic symptoms	: No chronic health hazards are likely for this material.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: Harmful to aquatic life. Toxic to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Hazardous to the aquatic environment, short-term (acute)	: Not applicable.
Hazardous to the aquatic environment, long-term (chronic)	: Not applicable.

Acetone (67-64-1)

NOEC (chronic)	≥ 79 mg/l Daphnia magna (Water flea)
----------------	--------------------------------------

heptane, n-heptane (142-82-5)

EC50 - Crustacea [1]	3.9 mg/l
LOEC (chronic)	0.32 mg/l Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Daphnia magna Duration: '21 d'

tert-butyl acetate (540-88-5)

LC50 - Fish [1]	240 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	350 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	16 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	6.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	64 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	5.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

BadAss Super Sheen Tire Shine

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable.
Carbon dioxide (CO2) (124-38-9)	
Persistence and degradability	Biodegradation is not applicable to inorganic compounds.
heptane, n-heptane (142-82-5)	
Persistence and degradability	Readily biodegradable.
tert-butyl acetate (540-88-5)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

BadAss Super Sheen Tire Shine	
Bioaccumulative potential	Potentially bioaccumulable.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Dispose in a safe manner in accordance with local/national regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1950	UN1950	1950	1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description			
UN1950 Aerosols, 2.1	UN1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

DOT	TDG	IMDG	IATA
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
UN-No. (DOT) : UN1950

TDG
UN-No. (TDG) : UN1950
Emergency Response Guide (ERG) Number : 126

IMDG
No data available

IATA
No data available

SECTION 15 Regulatory information

15.1. Federal regulations

BadAss Super Sheen Tire Shine	
SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Acetone (67-64-1)	
CERCLA RQ	5000 lb

tert-butyl acetate (540-88-5)	
CERCLA RQ	5000 lb

15.2. International regulations

No additional information available

BadAss Super Sheen Tire Shine

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date : 7/15/2026

Issue date : 7/15/2026

Full text of hazard classes and H-statements

H222	Extremely flammable aerosol
H229	Pressurized container; may burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Indication of changes:

New SDS.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.